



## To deliver from stock

### ANSI-flanged ball valves

soft seated ANSI flanged ball valve

body	WCB / CF8M other materials on request
inner parts	SUS304 / SUS316
seat sealing	PTFE glass re-inforced
flanges	acc. ANSI B16.5
operation	hand lever, automation optional
pressure rating	on stock: class 150, 300 and 600
size	1/2" - 12", up to 8" assorted on stock
subject to goods being unsold.	



### V-port segment valve

Wafer- or Flange-Type Version

body	CF8M/1.4408 WCB on request available
inner parts	SUS316
seat sealing	316/Stellite
flanges	Wafer or flanges acc. DIN EN 558-1 S1
operation	hand lever, automation optional
pressure rating	PN 16, 40
size	DN25 - DN200 (up to DN100 on stock)
subject to goods being unsold.	



### 3-pieces metal seated ball valve

body	WCB/1.0619 or CF8M/1.4408 other materials on request
inner parts	SUS630 / 1.4542
seat sealing	stainless steel with Tungsten carbide coating
flanges	BSP and BW/ISO
operation	hand lever, automation optional
pressure rating	ANSI class 600 / PN 100
size	DN15 - DN50
subject to goods being unsold.	



### Globe valve

with or without bellow

body	GS-C25 / WCB 1.4408
inner parts	A182 F6
seat sealing	metallic
flanges	DIN EN 558-1 S1 (= DIN 3202 F1)
operation	hand wheel
pressure rating	PN 40

size DN15 - DN200 (until DN100 on stock)  
subject to goods being unsold.



---

### 3-way ball valve

with full bore, all ways sealed, L- or T-bore ball, automatable

body 1.4408 / CF8M  
top flange according ISO 5211  
inner parts 1.4401  
seat sealing PTFE - glass reinforced  
flanges DIN  
operation hand lever, automation optional  
pressure rating PN 10/40, from DN65 PN16  
size DN15 - DN100

subject to goods being unsold.



---

### Metal seated flanged ball valve

type JBFM, according DIN and ANSI, full bore, bi-directional  
sealing system, applicable until 450°

body 1.4408 / CF8M  
ball 1.4408 / wolframcarbid coated  
inner parts 1.4980  
seat sealing 1.4408 / wolframcarbid coated  
flanges DIN /EN 1092-1 Form B  
operation hand lever, automation optional  
pressure rating PN 10/40 on stock, PN100 on request

ANSI 150lbs on stock, 300 / 600 lbs on  
request

face to face according EN558 row 14,15

size DN15 - DN100

subject to goods being unsold.



---

### Hastelloy - ball valve

3 pieces ball valve, antistatic, full bore with ISO butt weld ends

body Hastelloy C22  
ball Hastelloy C22  
inner parts Hastelloy C22  
seat sealing TFM  
body sealing PTFE  
connections ISO BW, Hastelloy C22  
size DN15 - DN50

subject to goods being unsold.



---

### Strainer

Y-Form, stainless steel and carbon steel, DIN flanges or butt

weld, standard or fine screen  
body 1.4408/CF8M or WCB A216  
screen 1.4401  
cap sealing graphite / 1.4401  
flanges DIN /EN 1092-1 Form B  
pressure rating PN 16/40  
face to face according EN558-1  
size DN15 - DN200  
subject to goods being unsold.

---



**Are you interested? Are you interested in continuative documents?**

**Please contact us by phone, e-mail or fax.**

**We are pleased to support you.**

**Zuercher Technik AG**

---

**Zuercher Technik AG**  
Neumattstrasse 6  
CH-4450 Sissach

Tel. +41 (0)61 975 10 10  
Fax +41 (0)61 975 10 50  
[www.zuercher.com](http://www.zuercher.com)  
[E-Mail](mailto:info@zuercher.com)

---

[Unsubscribe from this newsletter list](#)