



New on stock

Globe valve

with or without bellow

body	GS-C25 / WCB 1.4408
inner parts	A182 F6
seat sealing	metallic
flanges	DIN EN 558-1 S1 (= DIN 3202 F1)
operation	hand wheel
pressure rating	PN 40
size	DN15 - DN200 (until DN100 on stock)



subject to goods being unsold.

3-way ball valve

with full bore, all ways sealed, L- or T-bore ball, automatable

body	1.4408 / CF8M
top flange	according ISO 5211
inner parts	1.4401
seat sealing	PTFE - glass reinforced
flanges	DIN
operation	hand lever, automation optional
pressure rating	PN 10/40, from DN65 PN16
size	DN15 - DN100



subject to goods being unsold.

Metal seated flanged ball valve

type JBFM, according DIN and ANSI, full bore, bi-directional sealing system, applicable until 450°

body	1.4408 / CF8M
ball	1.4408 / wolframcarbid coated
inner parts	1.4980
seat sealing	1.4408 / wolframcarbid coated
flanges	DIN /EN 1092-1 Form B
operation	hand lever, automation optional
pressure rating	PN 10/40 on stock, PN100 on request ANSI 150lbs on stock, 300 / 600 lbs on request
face to face	according EN558 row 14,15
size	DN15 - DN100

subject to goods being unsold.



Hastelloy - ball valve

3 pieces ball valve, antistatic, full bore with ISO butt weld ends

body	Hastelloy C22
ball	Hastelloy C22
inner parts	Hastelloy C22
seat sealing	TFM
body sealing	PTFE
connections	ISO BW, Hastelloy C22
size	DN15 - DN50



subject to goods being unsold.

Strainer

Y-Form, stainless steel and carbon steel, DIN flanges or butt weld, standard or fine screen

body	1.4408/CF8M or WCB A216
screen	1.4401
cap sealing	graphite / 1.4401
flanges	DIN /EN 1092-1 Form B
pressure rating	PN 16/40
face to face	according EN558-1
size	DN15 - DN200



Are you interested? Are you interested in continuative documents?

Please contact us by phone, e-mail or fax.

We are pleased to support you.

Zuercher Technik AG

Zuercher Technik AG
Neumattstrasse 6
CH-4450 Sissach

Tel. +41 (0)61 975 10 10
Fax +41 (0)61 975 10 50
www.zuercher.com
E-Mail

[Unsubscribe from this new sletter list](#)